SDS Sheet Supplied by:





Date of Issue: 22 September 2014

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

RM Number: 8010

RM Name: Sand for Sieve Analysis

RM Parts: Material A, Material C, and Material D

Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Reference Material (RM) is intended to serve as a test material in the sieve analysis of granular materials. A unit of RM 8010 consists of a three-bottle set of sands covering three size distributions. Each bottle contains approximately 130 g of sand, enough for the sample sizes designated in ASTM C 429 Standard Test Method for Sieve Analysis of Raw Materials for Glass Manufacture.

Material A is a test material for the coarser sieves, No. 30 to No. 100 (600 μm to 150 μm)

Material C is for the midrange, No. 70 to No. 200 (212 μ m to 75 μ m) Material D is for the finer sieves, No. 100 to No. 325 (150 μ m to 45 μ m)

Company Information

National Institute of Standards and Technology Standard Reference Materials Program 100 Bureau Drive, Stop 2300 Gaithersburg, Maryland 20899-2300

 Telephone:
 301-975-2200
 Emergency Telephone ChemTrec:

 FAX:
 301-948-3730
 1-800-424-9300 (North America)

 E-mail:
 SRMMSDS@nist.gov
 +1-703-527-3887 (International)

Website: http://www.nist.gov/srm

2. HAZARDS IDENTIFICATION

Note: This material consists of sieved sand intended for use as a test material. The health and safety information provided in this SDS are for repeat exposures to silica, crystalline quartz in the form of respirable dust.

Classification

Physical Hazard: Not Classified.

Health Hazard: Carcinogenic Category 1 STOT, Repeated Exposure Category 1

Label Elements



Signal Word DANGER

Hazard Statement(s)

H350 May cause cancer (lung) via inhalation.

H372 Causes damage to lungs through prolonged or repeat inhalation.

RM 8010 Page 1 of 6

Precautionary Statement(s)

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear eye protection, protective gloves and clothing.
P308+P313	If exposed or concerned: Get medical attention.

P405 Store locked up.

P501 Dispose of contents and container according to local regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients(s) with Unknown Acute Toxicity: Not applicable.

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Sand

Other Designations: Quartz; alpha-quartz; silicon dioxide; silica; white crystal sand.

Components are listed in compliance with OSHA's 29 CFR 1910.1200.

Component	CAS Registry	EC Number (EINECS)	Nominal Concentration (%)
Silica, crystalline quartz	14808-60-7	238-878-4	100

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: Wash skin with soap and water.

Eye Contact: Flush eyes with water for at least 15 minutes. If necessary, seek medical attention.

Ingestion: If adverse effects occur after ingestion, seek medical treatment.

Most Important Symptoms/Effects, Acute and Delayed: Prolonged exposure to respirable silica particles can cause lung damage (silicosis) and cancer.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek medical attention if needed.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Negligible fire hazard. Avoid generating dust. See Section 9, "Physical and Chemical Properties" for flammability properties.

Extinguishing Media:

Suitable: Regular dry chemical, carbon dioxide, water, regular foam.

Unsuitable: None listed.

Specific Hazards Arising from the Chemical: None listed.

Special Protective Equipment and Precautions for Fire-Fighters: Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1 Fire = 0 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Any accumulated material on surfaces should be removed and properly disposed of. Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection".

Methods and Materials for Containment and Clean up: Collect spilled material in appropriate container for disposal. Keep out of water supplies and sewers. Keep unnecessary people away, isolate hazard area and deny entry.

RM 8010 Page 2 of 6

7. HANDLING AND STORAGE

Safe Handling Precautions: Minimize dust generation and accumulation on surfaces. Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces. See Section 8, "Exposure Controls and Personal Protection". Avoid contact with incompatible materials (see Section 10, "Stability and Reactivity").

Storage: Store and handling in accordance with all current regulations and standards.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits					
Components	OSHA (PEL)	ACGIH (TLV)	NIOSH (REL)		
Silica, crystalline quartz	TWA: 30/(%SiO ₂ + 2) mg/m ³ (total dust) TWA: 10/(%SiO ₂ + 2) mg/m ³ (respirable fraction) TWA: 250/(%SiO ₂ + 5) mppcf (respirable fraction)	TWA: 0.025 mg/m ³ (respirable fraction)	TWA: 0.05 mg/m ³ (respirable dust) IDLH: 50 mg/m ³ (respirable dust)		

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles with a face shield. An eye wash station should be readily available near areas of use.

Skin and Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Descriptive Properties	Sand
Appearance (physical state, color, etc.)	white or tan, granular powder
Molecular Formula	SiO_2
Molar Mass (g/mol)	60.09
Odor	odorless
Odor threshold	not available
pН	6 to 8
Evaporation rate	not applicable
Melting point/freezing point	1610 °C (2930 °F)
Density as specific gravity (water =1)	$2.65 \text{ g/mL}^{(a)}$
Vapor Pressure	none
Vapor Density (air = 1)	not applicable
Viscosity (cP)	not applicable
Solubility(ies)	insoluble in water, acids, organic solvents;
	soluble in hydrofluoric acid (produces a corrosive gas, silicon tetrafluoride);
	slightly soluble in alkali, hot concentrated phosphoric acid.
Partition coefficient (n-octanol/water)	not available

RM 8010 Page 3 of 6

Descriptive Properties Sand Material A is 600 µm to 150 µm; **Nominal Particle Size** Material C is 212 μm to 75 μm; Material D is 150 μm to 45 μm. **Thermal Stability Properties Autoignition Temperature** not applicable **Thermal Decomposition** not applicable 2230 °C (4046 °F) Initial boiling point and boiling range **Explosive Limits, LEL (Volume %)** not applicable **Explosive Limits, UEL (Volume %)** not applicable **Flash Point** not applicable not applicable Flammability (solid, gas) (a) Properties listed in the vendor MSDS. 10. STABILITY AND REACTIVITY **Reactivity:** Stable at normal temperatures and pressure. Stability: X Stable Unstable Possible Hazardous Reactions: None listed. Conditions to Avoid: Avoid generating dust. Avoid heat, flames, sparks, and other sources of ignitions. Avoid contact with incompatible materials. Incompatible Materials: Bases, halogens, acids, metal salts, metals, oxidizing materials, combustible materials. **Fire/Explosion Information:** See Section 5, "Fire Fighting Measures". Hazardous Decomposition: Thermal decomposition will produce miscellaneous compounds. Hazardous Polymerization: Will Occur X Will Not Occur 11. TOXICOLOGICAL INFORMATION X Inhalation X Skin **Route of Exposure:** Symptoms Related to the Physical, Chemical and Toxicological Characteristics: May aggravate respiratory disorders. Potential Health Effects (Acute, Chronic, and Delayed) Inhalation: Irritation, cough phlegm. Prolonged or repeated exposure to mixtures containing respirable silica may cause cough, expectoration, dyspnea, wheezing, pharyngitis, chronic bronchitis, emphysema, and silicosis. **Skin Contact:** May cause mechanical irritation. Eye Contact: May cause irritation or eye damage. **Ingestion:** May cause irritation. **Numerical Measures of Toxicity Acute Toxicity:** Not classified. Skin Corrosion/Irritation: No data available. Serious Eye Damage/Eye Irritation: No data available. Respiratory Sensitization: No data available. **Skin Sensitization:** No data available.

RM 8010 Page 4 of 6

Germ Cell Mutagenicity: No data available.

Carcinogenicity: Category 1.

Listed as a Carcinogen/Potential Carcinogen

X Yes

No

Silica, crystalline quartz is listed as Group 1, *carcinogenic to humans* by IARC, *known human carcinogen* (respirable size) by NTP, and is not listed by OSHA as a designated carcinogen.

Tumorigenic data: Rat, Inhalation, TCLo: 50 mg/m³ (6 h)

Mutagenic data: Human, 120 mg/L (24 h)

Reproductive Toxicity: No data available.

Specific Target Organ Toxicity, Single Exposure: No data available.

Specific Target Organ Toxicity, Repeated Exposure: Category 1, Lungs.

Repeated and prolonged exposure to respirable quartz may cause chronic bronchitis, emphysema, and

silicosis.

Aspiration hazard: Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity Data: No data available.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of waste in accordance with all applicable federal, state, and local regulations.

14. Transportation Information

U.S. DOT and IATA: Not regulated by DOT or IATA.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Not regulated.

SARA Title III Section 302 (40 CFR 355.30): Not regulated.

SARA Title III Section 304 (40 CFR 355.40): Not regulated.

SARA Title III Section 313 (40 CFR 372.65): Not regulated.

OSHA Process Safety (29 CFR 1910.119): Not regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH: No CHRONIC HEALTH: Yes FIRE: No REACTIVE: No PRESSURE: No

State Regulations:

California Proposition 65: Warning! This product contains a chemical (quartz) known to the state of California to cause cancer.

U.S. TSCA Inventory: Quartz is listed.

TSCA 12(b), Export Notification: Quartz is not listed.

Canadian Regulations: WHMIS Information is not provided for this material.

RM 8010 Page 5 of 6

16. OTHER INFORMATION

Issue Date: 22 September 2014

Sources: ChemADVISOR, Inc., SDS, Quartz, 21 March 2014.

U.S. Silica Company, Material Safety Data Sheet, Silica Sand and Ground Silica, March 2012.

UNIMIN Corporation, Material Safety Data Sheet, MSDS No: 011-U, May 2009.

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists	NRC	Nuclear Regulatory Commission
ALI	Annual Limit on Intake	NTP	National Toxicology Program
CAS	Chemical Abstracts Service	OSHA	Occupational Safety and Health Administration
CERCLA	Comprehensive Environmental Response,	PEL	Permissible Exposure Limit
	Compensation, and Liability Act		
CFR	Code of Federal Regulations	RCRA	Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EC50	Effective Concentration, 50 %	RM	Reference Material
EINECS	European Inventory of Existing Commercial	RQ	Reportable Quantity
	Chemical Substances		
EPCRA	Emergency Planning and Community Right-to-Know	RTECS	Registry of Toxic Effects of Chemical Substances
	Act		
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transportation Agency	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
LC50	Lethal Concentration, 50 %	STEL	Short Term Exposure Limit
LD50	Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
NIOSH	National Institute for Occupational Safety and Health	UEL	Upper Explosive Limit
NIST	National Institute of Standards and Technology	WHMIS	Workplace Hazardous Materials Information System

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The reference values for this material are given in the NIST Report of Investigation.

Users of this RM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at http://www.nist.gov/srm.

RM 8010 Page 6 of 6