



Schmidt Test Hammer Selection

Model	Description	Compressive Strength	Impact Energy
<u>HM-75</u>	Original Schmidt, Type N	1,450—10,152psi (10—70mPa)	2.207Nm (1.63ft-lbf)
<u>HM-75L</u>	Original Schmidt, Type L	1,450—10,152psi (10—70mPa)	0.735Nm (0.54ft-lbf)
<u>HM-84</u>	Original Schmidt Live, Type N	1,450—10,152psi (10—70mPa)	2.207Nm (1.63ft-lbf)
<u>HM-84L</u>	Original Schmidt Live, Type L	1,450—10,152psi (10—70mPa)	0.735Nm (0.54ft-lbf)
<u>HM-82</u>	Rock Schmidt, Type N	2,900—21,750psi (20—150mPa)	2.207Nm (1.63ft-lbf)
<u>HM-82L</u>	Rock Schmidt, Type L	2,900—21,750psi (20—150mPa)	0.735Nm (0.54ft-lbf)
<u>HM-89</u>	Silver Schmidt, Type N	1,450—14,500psi (10—100mPa) ¹	2.207Nm (1.63ft-lbf)
<u>HM-89L</u>	Silver Schmidt, Type L	1,450—14,500psi (10—100mPa)	0.735Nm (0.54ft-lbf)
<u>HM-89L</u>	Silver Schmidt, Type L with Mushroom Plunger Accessory	725 to 4,351psi (5 to 30mPa)	0.735Nm (0.54ft-lbf)

¹Up to 17,405psi (120mPa) with user-defined correlation



Order by Phone: 800.444.1508 / 740.548.7298 • Order Online: www.globalgilson.com

