



Standard Concrete Compression Testing Machines

Controller	Model ²	Total Capacity lbf (kN)	Maximum psi, 6x12in Cylinder	Overall Size with Stand WxDxH, in	Opening with Platens WxH, in	Lower Platen Dimensions, in
Pro	MC-250P	250 (1,112)	7,000	27 x 14 x 58	9.3 x 13.4	6.5 dia. x 1.9
	MC-300P	300 (1,335)	8,500	29 x 16 x 60	9.5 x 14.4	9 x 11 x 1.9
	MC-400P	400 (1,780)	11,300	39 x 20 x 61	13.3 x 14.3	12 x 18 x 2
	MC-500P	500 (2,224)	14,100	31 x 24 x 61	14 x 14.3	13 x 18 x 2
Pro-Plus	MC-250PR	250 (1,112)	7,000	27 x 17 x 57	9.3 x 13.4	6.5 dia. x 1.9
	MC-300PR	300 (1,335)	8,500	32 x 17 x 59	9.5 x 14.4	9 x 11 x 1.9
	MC-400PR	400 (1,780)	11,300	39 x 20 x 61	13.3 x 14.3	12 x 18 x 2
	MC-500PRP¹	500 (2,224)	14,000	30 x 24 x 69	14 x 26.8	13 x 18 x 2
	MC-500PR	500 (2,224)	14,100	31 x 24 x 61	14 x 14.3	13 x 18 x 2

¹ Frames configured for 2-Block masonry prisms. ² Specify 230V/50Hz operation by adding an "F" suffix to the model number.



Order by Phone: 800.444.1508 / 740.548.7298



Order Online: globalgilson.com

